

all.13

MTI
LINE 35
SP 215-I, LP O-II
24 FOLD CDPSUM

1 KILOMETER

SOUTHEAST

AREA BR-109 (ADRIATIC SEA) MINERARIA TEXAS ITALIAN

LINE NO. 35 SP's 215-I, LP O-II

PROCESSING FIELD DATA

<input checked="" type="checkbox"/> EXPONENTIAL GAIN RATE 450 Sec. GATE 0-3.0 Sec.	<input checked="" type="checkbox"/> VELOCITY ANALYSIS	RECORDING INST. TI 11,000, CFS III, 48 TRACE
<input checked="" type="checkbox"/> VERTICAL STACK TWO ON ONE	<input checked="" type="checkbox"/> REGIONAL NORMAL MOVEMENT	RECORDING FILTERS 8-62 cps
<input checked="" type="checkbox"/> NORMAL MOVEMENT	<input checked="" type="checkbox"/> COMMON DEPTH POINT GATHER	SPREAD CONFIGURATION - END ON 585'-829' OFFSET
<input checked="" type="checkbox"/> T.V. DECON <input type="checkbox"/> MULTICHANNEL DECON	<input checked="" type="checkbox"/> COMMON DEPTH POINT SUM 24 FOLD	GAIN INFORMATION - BINARY GAIN
SP 215-I, LP O-II FILTERS 1 WHITE NOISE 1%	<input checked="" type="checkbox"/> DIGITAL FILTER NO FILTERS 3	ARRAY - 19 GUNS
FILTER LENGTH 355 ms	BAND PASS 15-55 cps TIME 0-500 sec	2-80 IN ² 401 6-20 IN ²
DESIGN GATES NEAR OFFSET 200-4000 Sec	10-40 cps 100 sec	6-40 IN ² 5-10 IN ²
DESIGN GATES FAR OFFSET 200-4000 Sec	10-25 cps 2,100 sec	
SP NO FILTERS WHITE NOISE	<input checked="" type="checkbox"/> TRACE AMPLITUDE EQUALIZATION	RECORDED AND PROCESSED BY
FILTER LENGTH ms	<input type="checkbox"/> SINGLEFOLD DISPLAY	
DESIGN GATES NEAR OFFSET	<input checked="" type="checkbox"/> VELOCITY ANALYSIS	
DESIGN GATES FAR OFFSET		

MTI
LINE 35
SP 215-I, LP O-II
24 FOLD CDPSUM

